

Intelligent

**The trusted independent experts for hand dryers
and washrooms since 2012.**





Dryflow[®] Bi-Tap

- High speed, low energy
- Plug in system for easy installation and servicing
- Adjustable noise levels
- Keeps everything over the sink, improving hygiene & health and safety
- Reduced time improves washroom traffic flow



Recommended
300+
uses a day



Dry Time
15
seconds



Guarantee
3
years



Designed to work alongside the Dryflow[®] Bi-Tap sensor operated water and soap dispenser tap (IFSGAJ002A-ANON), as well as on its own.

Dries possible per £1	4,761
Electrical Supply Voltage	220-240 V
Electrical Supply Frequency	50/60 Hz
Expected Motor Life	3000 Hours
Rated Power	0.42 kW - 1.5 kW (Internal on / off heater switch & adjustable motor speed)
Approx. Watt-Hours per Dry	1.75 Wh - 6.25 Wh
Heater Element Power	0.4 kW
Operating Sound Level	67-72 dB
Motor Speed	30,000 RPM
Air Speed	248 MPH
Operating Temperature Range	At ambient temp (25°C) - 42°C
Motor Cut off Time	60 seconds
Motor Class	Class I
Materials	Chrome plated brass
Finishes Available & Codes	Polished Chrome (IFSM092A-ANON)
IP Rating	IP23
Cable Entry Point	Rear entry with access available from bottom
Certifications and Awards	CE, ROHS, TUV-GS