



DB250 / DB275

## DOLPHIN TEMPERATURE ADJUSTABLE INFRARED TAP

- › WRAS Approved product
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- › Water Supply: hot and cold supply featuring temperature adjustment lever
- › Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Tap settings may be adjusted by using remote control (DB51)
- › To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
- › 2 year manufacturer's warranty
- › Power connections: tap: male / power source: female
- › Complies with SKA rating criteria
- › The two flexible connectors contain integral check (non-return) valves
- › We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this tap
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.

<b>HEIGHT</b>	<b>142MM</b>
<b>DIAMETER</b>	<b>50MM</b>
<b>PROJECTION</b>	<b>60MM</b>

### PRODUCT CODES

- DB250C Polished chrome battery powered
- DB250S-2 Brushed satin battery powered
- DB275C Polished chrome transformer powered
- DB275S-2 Satin brushed transformer powered

